


Product Data Sheet

Alfresco Timber Oil



Product	Alfresco Timber Oil: For Outdoor Furniture
Size	250ml, 1L & 4L
Description	<p>A tung oil based finish for outdoor timber and furniture. It has added UV protection to battle the harsh sunlight we receive in Australia! With that said, it is best used for timber that is protected, eg. under alfresco, shade cloth and verandas.</p> <p>The formula is built around natural oils such as tung oil which helps to seal timber and protects it from water damage and other wear. It is a great product to seal and finish new timber, but also to revive older timber that is looking dry and worn.</p> <p>This oil contains no lacquer or silicon, unlike many products on the market, which means easier maintenance for you and a beautiful natural finish.</p>
Used For	Alfresco timber & furniture, timber trims & frames, outdoor tables, window sills & more.
Surface Preparation	<p>Ensure the surface is clean and dry before application. D-limonene (natural citrus solvent) or a turpentine can be used for a vigorous clean. For a lighter clean, you can use an all purpose cleaner.</p> <p>If there is any oil, wax, grease, dirt or similar residue on the surface, it may affect the tung oil's ability to cure - so a thorough clean is important.</p>
How to Apply	<ol style="list-style-type: none">1. Rub or brush oil into the timber. Lighter coats are better.2. On the first coat, let it sit for 5 minutes after applying. Wipe on more oil to areas that become dull, as the oil soaks in.3. After 5 more minutes, wipe off any excess oil with another clean cloth and rub it back vigorously.4. Follow this procedure for each coat. <i>Note: Some people prefer to wet sand between coats, however this is generally only for timber that is quite porous.</i>5. Apply 3 coats. Best to wait 24 hours between coats. Apply more coats if desired or necessary.6. Hang out any rags or soak in water, rather than leaving scrunched up, as there is the potential for combustion.

<p>Dry Time</p>	<p>24 hours to dry between coats. As this is tung oil based, it can take 4 weeks to completely cure. Light usage is however perfectly fine within this time.</p>
<p>Maintenance</p>	<p>This product is built from natural oils, in particular tung oil. This makes for a beautiful natural finish. If you do find the finish gets scratched or damaged, you can simply reapply following the same steps outlined above. There is no need to sand it back as you would with lacquers, varnishes and silicon based products.</p> <p>For general maintenance and wear, you can assess as you see fit. We would recommend reapplying a light 1-2 coats every 6-12 months to keep your timber looking fresh.</p>
<p>Clean Up</p>	<p>D-Limonene or mineral turpentine.</p>
<p>Safety</p>	<ul style="list-style-type: none"> ● Use in a well ventilated area. Wear a protective mask, if in enclosed space. ● Gloves are recommended ● Hang out rags to dry, or soak in water. Don't leave scrunched up. ● May contain traces of bee pollen & soy ● Contact Gilly's for SDS
<p>Ingredients</p>	<p>Tung oil, plant oils, eucalyptus essential oil, citrus terpene, UV stabiliser, soy bio-solvent, low odour solvent</p>
<p>Image</p>	

W: www.gillysaustralia.com.au
E: orders@gillysaustralia.com.au
Ph: (08) 9295 1973