

Product Data Sheet

Liquid Beeswax



Label Heading	Liquid Beeswax
Sizes	250ml, 1L, 2L & 4L
Description	A versatile furniture oil, enriched with beeswax designed to penetrate and nourish dry timber. Ideal for all types of timber and cane furniture. Food safe for kitchen use as well. Liquid Beeswax contains a citrus terpene that inhibits mould growth and smells amazing.
Used For	Raw timber to nourish and prevent cracking/splitting.
Surface Preparation	Ensure the surface is clean and dry before application.
How to Apply	<ol style="list-style-type: none"> 1. Apply with a soft cloth (or brush for carved/irregular areas). 2. Let it be absorbed by the timber for 5 minutes, before buffing back with another clean cloth. 3. Apply 3 coats, if timber is new or dry, repeating the same procedure. Subsequent coats can be applied straight after buffing. Each timber will vary in porosity and dryness, so the number of coats required will vary. Once timber is saturated, there is no need for any more. Take care not to over-apply; residue can become sticky and attract dirt.
Dry Time	Dry time between coats is 5-10 minutes to allow oil to soak in. Allow up to 30 minutes for a completely dry finish.
Maintenance	Gilly's Liquid Beeswax can be reapplied as frequently as required (if the timber becomes dull or dry). There is no need for any extra work, just follow the simple steps above. We would recommend reapplying a light coat every 4-6 months to keep your timber looking fresh. The more oil that has been applied over time, the less it will require for maintenance.
Clean Up	Warm, soapy water for hands and application cloths.
Safety	<ul style="list-style-type: none"> ● Food Safe ● Hang out rags to dry, or soak in water. Don't leave scrunched up. ● May contain traces of bee pollen & soy ● Contact Gilly's for SDS

Ingredients	Plant oils, beeswax, citrus terpene (d-Limonene)
Image	

W: www.gillysaustralia.com.au
E: orders@gillysaustralia.com.au
T: (08) 9295 1973