

Image Intensifier specification
18 millimetre micro-channel wafer
ECHO
ZG0124B



184-7386A0

Page 1 of 2

Description

The Image Intensifier Assembly, 18 millimetres micro-channel wafer, shall have a minimum useful photocathode and phosphor screen diameter of 17.0 millimetres (mm). The assembly shall employ a micro-channel electron multiplier plate with proximity focus on the input and output. The assembly shall include the high voltage multiplier and oscillator and shall be encapsulated within a hard surface insulating sleeve or boot and assembled in a hard plastic housing. The tube is equipped with **AUTO-GATING**

Phosphor : P43 or P22

Input window : Glass

Output window : Inverting fibre-optic

Construction

The assembly shall be fabricated in accordance with the applicable drawing 183-0124A*.

Limiting values

	<u>Minimal</u>	<u>Maximal</u>	<u>Unit</u>
Continuous input Supply voltage	2.0	3.5	V
Reversed Polarity (60 sec)	-3.7	+3.7	V
Storage temperature long term	-35	+35	°C
Operating temperature (4 hours max.)	-33	+49	°C
Force on bearing surface	200		N

Operating conditions and characteristics

Operating Supply voltage : 2.7 V

Ambient temperature : 20 ± 1°C

When the image intensifier is operated under the conditions mentioned above, unless otherwise specified, the characteristic values that follow are attainable:

Date
March 20, 2018

Signed
BJE

Checked
OR

184-7386A0

Image Intensifier specification
 18 millimetre micro-channel wafer
ECHO
ZG0124B



184-7386A0

Page 2 of 2

Property of the Photonis Group.
 Reproduction, or disclosure to third parties,
 in any form whatsoever not allowed without
 written consent of Photonis.

Propriété du groupe Photonis.
 La reproduction ou la diffusion à une tierce partie, sous
 quelque forme que ce soit, sans accord écrit de Photonis, est
 strictement interdite.

Eigendom van de Photonis Groep.
 Vermengvuldigen of mededeling aan derden, in welke vorm
 ook is zonder schriftelijke toestemming van Photonis niet
 geoorloofd.

	Minimal	Typical	Maximal	UNIT
FOM	1500		1800	
Signal to noise ratio	24			
(Photocathode illuminance 108 μ lx)				
Gain at $2 \cdot 10^{-5}$ lx	9000		15000	cd/m ² /lx
Gain at $2 \cdot 10^{-6}$ fc	(28260)		(47100)	fL/fc
Maximum Output Brightness	6		10	cd/m ²
Maximum Output Brightness	(1.8)		(2.9)	fL
Input current at $2 \cdot 10^{-5}$ lx			35	mA
Limiting resolution at centre	57		74	lp/mm
Limiting resolution at >200 lux	50			lp/mm
(=autogating mode)				
Burn-in	50			hours
Shear distortion		60		μ m
Gross distortion		75		μ m
Useful cathode diameter	17.0			mm
Halo (illumination spot 0.35mm)			0.95	mm
Image alignment			0.5	mm

Spots:

Maximum number of dark spots will be according to the following table:

SPOTS DIAMETER IN MICROMETERS	ZONE 1		
	dia. 5.6mm	dia. 5.6mm-14.7mm	dia 14.7mm-17.0mm
➤ 300	0	0	0
230 – 300	0	1	2
150 – 230	1	2	4
75 – 150	2	4	6

In case the assembly has more numerous dark spots of smaller dimension within a zone, the total quantity of dark spots in the zone should be within the total quantity of dark spots in the considered zone as specified in the above table.

For example, if a tube is showing [5 Ø75-150µm] dark spots in zone 2 instead of the [4 Ø75-150µm + 2 Ø150-230µm] specified ones, the tube will be considered to be compliant with the specification.

Date March 20, 2018	Signed BJE	Checked OR	184-7386A0
------------------------	---------------	---------------	------------