

Image Intensifier specification
18 millimetre micro-channel wafer
ECHO Plus
ZG0124C



184-7388A1

Page 1 of 2

Description

The Image Intensifier Assembly, 18 millimetres micro-channel wafer, shall have a minimum useful photocathode and phosphor screen diameter of 17.0 millimetres (mm). The assembly shall employ a micro-channel electron multiplier plate with proximity focus on the input and output. The assembly shall include the high voltage multiplier and oscillator and shall be encapsulated within a hard surface insulating sleeve or boot and assembled in a hard plastic housing. The tube is equipped with **AUTO-GATING**

Phosphor : P43 or P22
Input window : Glass
Output window : Inverting fibre-optic

Construction

The assembly shall be fabricated in accordance with the applicable drawing 183-0124A*.

Limiting values

	<u>Minimal</u>	<u>Maximal</u>	<u>Unit</u>
Continuous input Supply voltage	2.0	3.5	V
Reversed Polarity (60 sec)	-3.7	+3.7	V
Storage temperature long term	-35	+35	°C
Operating temperature (4 hours max.)	-33	+49	°C
Force on bearing surface		200	N

Operating conditions and characteristics

Operating Supply voltage : 2.7 V
Ambient temperature : 20 ± 1°C

When the image intensifier is operated under the conditions mentioned above, unless otherwise specified, the characteristic values that follow are attainable:

Date
May 03, 2019

Signed
BJE

Checked
OR

184-7388A1

Image Intensifier specification
 18 millimetre micro-channel wafer
ECHO Plus
ZG0124C



184-7388A1

Page 2 of 2

Property of the Photonis Group.
 Reproduction, or disclosure to third parties,
 in any form whatsoever not allowed without
 written consent of Photonis.

Propriété du groupe Photonis.
 La reproduction ou la diffusion à une tierce partie,
 sous quelque forme que ce soit, sans accord écrit
 de Photonis, est strictement interdite.

Eigendom van de Photonis Groep.
 Vermenigvuldigen of mededeling aan derden, in
 welke vorm ook is zonder schriftelijke toestemming
 van Photonis niet geoorloofd.

	Minimal	Typical	Maximal	UNIT
FOM	2000			
Signal to noise ratio (Photocathode illuminance 108 μ lx)	25			
Gain at 2.10^{-5} lx	9000		15000	cd/m ² /lx
Gain at 2.10^{-6} fc	(28260)		(47100)	fL/fc
Maximum Output Brightness	6		10	cd/m ²
Maximum Output Brightness	(1.8)		(2.9)	fL
Input current at 2.10^{-5} lx			35	mA
Limiting resolution at centre	57			lp/mm
Limiting resolution at >200 lux (=autogating mode)	50			lp/mm
Burn-in	50			hours
Shear distortion			60	μ m
Gross distortion			75	μ m
Useful cathode diameter	17.0			mm
Halo (illumination spot 0.35mm)			0.95	mm
Image alignment			0.5	mm

Spots:

Maximum number of dark spots will be according to the following table:

SPOTS DIAMETER IN MICROMETERS	ZONE 1 dia. 5.6mm	ZONE 2 dia. 5.6mm-14.7mm	ZONE 3 dia 14.7mm-17.0mm
➤ 300	0	0	0
230 – 300	0	1	1
150 – 230	0	2	2
75 – 150	2	3	3

In case the assembly has more numerous dark spots of smaller dimension within a zone, the total quantity of dark spots in the zone should be within the total quantity of dark spots in the considered zone as specified in the above table.

For example, if a tube is showing [5 Ø75-150 μ m] dark spots in zone 2 instead of the [3 Ø75-150 μ m + 2 Ø150-230 μ m] specified ones, the tube will be considered to be compliant with the specification.

Date
May 03, 2019

Signed
BJE

Checked
OR

184-7388A1