



TR200 mitred

Demarcation / Railing

Heras Tangorail is a self-raking railing system with flexible panels that follow ground contours, providing optimum site safety and security.


Available with panel heights up to 2.4m, the TR200 features mitred heads on each bar for an imposing visual deterrence as well as practical physical security.

The versatile TR200 system has been awarded an SR1, and is listed in the Red Book.

The non-welded design allows for fast, uncomplicated installation, the TR200 comprises a hollow tube vertical bar system with top and bottom cross members, affixed between SHS posts.

- **Strong intrusion deterrent with SR1 rating**
- **Self-raking – no stepped panels and fewer posts**
- **Eco-friendly - no welding and low zinc content**
- **Added safety – no gaps under fence**
- **Fast installation and manufacturing**

Drawings



Technical specifications (dimensions in mm)

Type	Post centre-to-centre (A)	Panel height (B)	C	D	E	F	G	Post height (H)	Dig in depth (J)
TR200 180	2890	1750	100	125	225	150	50	2400	600
TR200 200	2890	1950	100	125	225	150	50	2600	600
TR200 210	2890	2050	100	125	225	100	50	2800	700
TR200 240	2890	2350	100	125	225	100	50	3100	700

Material	Steel
Colors	RAL 6005 (moss green) RAL 9005 (jet black) Multicolor (optional)
Finish	Pre-galvanized and coated
Vertical bar diameter	26 mm
Vertical bar centre-to-centre	125 mm
Top and bottom rail dimensions	55 x 52 mm
Post type (profile)	SHS (60 x 60 mm)
Verts per panel	22



Certificates

- Powder coating according to EN 13438 : 2005
- Steel used at grade DX51, galvanised to Z275
- Sheet steel hot dip coated as per EN 10346

Ordering information

Contact your local Heras office for precise ordering details.

Suggested accessories / products

- Quantum self-closing gate
- Pedestrian gate (single and double)
- Vehicle access swing gate