



Unit 2 North Way, Walworth Business Park, Andover, Hants SP10 5AZ, UK
 Tel: (44) 1264 332004 Fax: (44) 1264 355399
 email: enquiries@pumpsets.com Website: www.pumpsets.com

ATALANTA PELICAN 351
 3" x 3" Self Priming Diaphragm Sludge Pump
 with
 Lombardini 15LD225 Diesel Engine

Designed to Handle Mud, Sludge, Sewage and Other Thick Liquids that Flow



- Cast Aluminium for Portability and Durability
- Thermoplastic Rubber Diaphragm and Polyurethane Flap Valves
- Solids Handling up to 40 mm
- Continuous Dry Running without Damage
- Self Priming to 7.5 m
- Screwed BSP Male Connections
- Easy Cleanout & Maintenance
- Mounted on 2 Wheel Site Trolley
- Many Options Including – Spares Kits – Hoses – Suction Lance for Pit Latrines - Quick Couplings – Case Packing

Special Feature: Base of pump can be rotated through 90° for access through doors etc.

Powered by a Lombardini lightweight industrial air cooled single cylinder diesel engine model 15LD225 developing 2.7 kW at a nominal 2750 rpm complete with recoil start, (optional **E** – 12 volt electric start), 3 litre 4 hr. fuel tank, silencer, throttle, dry type air, oil and fuel filters. Set is supplied with Pump and Engine Operating and Instruction Manuals.

