



ULTRATECH
INTERNATIONAL, INC



ADA SIGN DEPOT A National Distributor UltraTech Truncated Domes

KEY FEATURES AND BENEFITS

- + Available in four (4) sizes: 2' x 2', 2' x 3', 2' x 4' and 2' x 5'.
- + Safety yellow color assists people with severe visual impairment. Black, brick red and safety red also available.
- + Flexible construction forms to fit dips, slopes and inclines in sidewalks and walkways.
- + Better slip resistance than composites.
- + Better impact resistance than composites.
- + UNBREAKABLE.
- + Ultra-ADA Pads are designed for the visually impaired to feel the raised, truncated domes with their feet. This, in combination with the tapping cane, can alert them to a different surface than the surrounding concrete sidewalk and an upcoming intersection.
- + Installs quickly and easily using adhesive and anchors (included). Flexible construction forms to fit dips, slopes and inclines in sidewalks and walkways.

Part# 0750, 0751, 0752, 0753, 0756, 0757, 0758, 0759, 0760, 0761, 0762, 0763, 0765, 0766, 0767, 0768

Dimensions ft. (mm) 2 x 2 (610 x 610), 2 x 3 (610 x 914), 2 x 4 (610 x 1,219), 2 x 5 (610 x 1,524)

Material Flexible Urethane

Precautions Product must be installed on dry surfaces
Product should be installed at temperatures between 40° F (4° C) to 100° F (38° C)

Recommended Maintenance Power washing approximately every six months

Test	ASTM Test Method	Value
Weatherometer Exposure	G155-05a	200 hours – no cracks
Corrosion Resistance	B117-07	200 hours – no corrosion or change in appearance
Tensile	D412-06a	Elongation at break, 400%
Abrasion Resistance	D4060-07	Ave Wt Loss, L 143.7 mg Ave Wear Index, I 144
Abrasion Resistance	C-501	1000 Cycles WI 292 2000 Cycles WI 336
"Slip Test"	C-1028-07	Static Coefficient of Friction – Dry = 1.16 Static Coefficient of Friction – Wet = 1.01

Ultra-ADA Pad, Urethane Model Specifications

